

## Axis product selection result



AXIS M1054



AXIS M1034-W



AXIS M1025



AXIS M1014



AXIS M1004-W

Camera					
Image sensor	CMOS	CMOS	CMOS	CMOS	CMOS
Image sensor size	1/4"	1/4"	1/2.7"	1/4"	1/4"
Megapixel sensor	✓	✓	✓	✓	✓
Sensor size in megapixel	1	1	1	1	1
Progressive scan	✓	✓	✓	✓	✓
Wide dynamic range			✓		
Min illumination/ light sensitivity (Color)	1.2 lux	1.2 lux	1.5 lux	1.2 lux	1.2 lux
Min illumination/ light sensitivity (B/W)					
Video					
Day and Night functionality					
Max video resolution	1280x800	1280x800	1920x1080	1280x800	1280x800
Max frames per second	30	30	30	30	30
Lens					
Focal length	2.8 mm	2.8 mm	2.8 mm	2.8 mm	2.8 mm
Varifocal					
Aperture	2	2	2	2	2
Horizontal field of view	84	80	84	80	80
Lens mount					
Lens changeable					
PTZ					
Mech. Pan/Tilt					
Digital Pan/Tilt	✓	✓	✓	✓	✓
Pan range					
Tilt range					
Guard tour	✓	✓		✓	✓
Optical zoom					
Digital zoom	✓	✓	✓	✓	✓
Compression					
Motion JPEG	✓	✓	✓	✓	✓
MPEG-4			✓		
H.264	✓	✓	✓	✓	✓
HDTV resolution	720p	720p	1080p	720p	720p
Audio					
Audio support	✓	✓			
Two-way audio	✓	✓			
Full duplex audio					
Built-in microphone	✓	✓			

Built-in speaker	✓	✓			
<b>System Integration</b>					
Video motion detection	✓	✓	✓	✓	✓
Audio detection	✓	✓			
Active tampering	✓	✓	✓	✓	✓
Alarm inputs/outputs	1/1	1/1		0/0	1/1
Serial connectors					
ONVIF	✓	✓	✓	✓	✓
Intelligent video capable					✓
AVHS	✓	✓	✓	✓	✓
<b>Network</b>					
QoS	✓	✓	✓	✓	✓
IPv6	✓	✓	✓	✓	✓
Power over Ethernet	✓		✓		
PoE class	2		1		
Wireless		✓			✓
<b>Security</b>					
Multi-level password	✓	✓	✓	✓	✓
HTTPS encryption	✓	✓	✓	✓	✓
IP address filtering	✓	✓	✓	✓	✓
IEEE 802.1X	✓	✓	✓	✓	✓
<b>General</b>					
IR LED(s)					
Slot for memory card			✓	✓	
Operational temperature °C	0 to 40	0 to 40	0 to 50	0 to 40	0 to 40
Vandal resistant					
IP rating					
Comments					