

## Axis product selection result



AXIS P5534-E



AXIS P5532-E



AXIS P5522-E



AXIS P5512-E

Camera				
Image sensor	CCD	CCD	CCD	CCD
Image sensor size	1/3"	1/4"	1/4"	1/4"
Megapixel sensor	✓			
Sensor size in megapixel	1.3			
Progressive scan	✓	✓	✓	
Wide dynamic range	✓	✓	✓	
Min illumination/ light sensitivity (Color)	0.74 lux	0.5 lux	0.5 lux	1 lux
Min illumination/ light sensitivity (B/W)	0.04 lux	0.01 lux	0.01 lux	0.3 lux
Video				
Day and Night functionality	✓	✓	✓	✓
Max video resolution	1280x720	720x576	720x576	704x480/704x576
Max frames per second	30/25	30/25	30/25	30/25
Lens				
Focal length	4.7 - 84.6 mm	3.6 - 104.4 mm	4.1 - 73.8 mm	3.8 - 46 mm
Varifocal				
Aperture	1.6	1.4	1.4	1.6
Horizontal field of view	55.2 - 3.2	53.1 - 2.0	48 - 2.8	51.6 - 4.4
Lens mount				
Lens changeable				
PTZ				
Mech. Pan/Tilt	✓	✓	✓	✓
Digital Pan/Tilt				
Pan range	+/-180	+/-180	+/-180	+/-180
Tilt range	180	180	180	180
Guard tour	✓	✓	✓	✓
Optical zoom	18	29	18	12
Digital zoom	12	12	12	4
Compression				
Motion JPEG	✓	✓	✓	✓
MPEG-4				
H.264	✓	✓	✓	✓
HDTV resolution	720p			
Audio				
Audio support				
Two-way audio				
Full duplex audio				
Built-in microphone				

Built-in speaker				
<b>System Integration</b>				
Video motion detection	✓	✓	✓	✓
Audio detection				
Active tampering				
Alarm inputs/outputs	0/0	0/0	0/0	0/0
Serial connectors				
ONVIF	✓	✓	✓	✓
Intelligent video capable	✓	✓	✓	✓
AVHS	✓	✓	✓	✓
<b>Network</b>				
QoS	✓	✓	✓	✓
IPv6	✓	✓	✓	✓
Power over Ethernet	✓	✓	✓	✓
PoE class	PoE+	PoE+	PoE+	3
Wireless				
<b>Security</b>				
Multi-level password	✓	✓	✓	✓
HTTPS encryption	✓	✓	✓	✓
IP address filtering	✓	✓	✓	✓
IEEE 802.1X	✓	✓	✓	✓
<b>General</b>				
IR LED(s)				
Slot for memory card	✓	✓	✓	✓
Operational temperature °C	-20 to 50	-20 to 50	-20 to 50	-20 to 50
Vandal resistant				
IP rating	IP66	IP66	IP66	IP66
Comments	* -	* -	* -	* -